

1" Turbojet Nozzles

- Flow setting at 100 psi (7 bar) operating pressure can be used for high pressure applications up to 580 psi (40 bar) hydrostatic pressure
- Raised bumper lug for straight stream pattern identification
- Compatible with Quick-Attack Foam Tube Style 755, See page 21

- 1701** 1" Turbojet Nozzle
- 1702** 1" Turbojet Nozzle with Pistol Grip
- 1703** 1" Turbojet Tip
- For use on Style 753 shutoff
- 1704** 1" Turbojet Nozzle with Pistol Grip
- 1711** 1" Turbojet Tip
- For use on Style 753 shutoff
 - Specify either 18-30 GPM or 13-23-30 GPM settings



Style 1702

| Style | Swivel Inlet | Length | Weight lbs. (kg) | Flow Settings | |
|-------|----------------|-----------------|------------------|------------------|--------------------|
| | | | | GPM | LPM |
| 1701 | 1 (25 mm) | 9 1/4" (206 mm) | 2 1/2 (1.1 kg) | 13-25-40-60 | 50-100-150-230 |
| 1702 | 1" (25 mm) | 9 1/4" (206 mm) | 3 (1.4kg) | 13-25-40-60 | 50-100-150-230 |
| 1703 | 1 1/2" (38 mm) | 6 5/8" (14 mm) | 1 3/4 (.8 kg) | 13-25-40-60 | 50-100-150-230 |
| 1704 | 1" (25 mm) | 9 1/4" (206 mm) | 3 (1.4 kg) | 18-30* 13-23-30* | 70-115* 50-90-115* |
| 1711 | 1 1/2" (38 mm) | 6 5/8" (14 mm) | 3 3/4 (1.7 kg) | 18-30* 13-23-30* | 70-115* 50-90-115* |

*Must specify



1 1/2" Turbojet Nozzles

- 100 psi (7 bar) standard, 75 psi (5 & 6 bar) optional
- Compatible with Quick Attack Foam Tube Style 766, See page 21

- 1714** 1 1/2" Turbojet Tip
- 1715** 1 1/2" Turbojet Nozzle
- 1716** 1 1/2" Turbojet Breakapart Nozzle
- Combination of Style 1717 tip + Style 2115 shutoff
- 1717** 1 1/2" Turbojet Tip with Twist Shutoff
- 1718** 1 1/2" Turbojet Breakapart Nozzle with Pistol Grip
- Combination of Style 1717 tip + Style 2116 shutoff
- 1720** 1 1/2" Turbojet Nozzle with Pistol Grip



Style 1717



Style 1720

| Style | Swivel Inlet | Length | Weight lbs. (kg) | Flow Settings | |
|-------|----------------|-----------------|------------------|---------------|-----------------|
| | | | | GPM | LPM |
| 1714 | 1 1/2" (38 mm) | 6 7/8" (165 mm) | 2 1/4 (1 kg) | 30-60-95-125 | 115-230-360-475 |
| 1715 | 1 1/2" (38 mm) | 9 1/2" (232 mm) | 3 1/2 (1.6 kg) | 30-60-95-125 | 115-230-360-475 |
| 1716 | 1 1/2" (38 mm) | 12" (295 mm) | 3 3/4 (1.7 kg) | 30-60-95-125 | 115-230-360-475 |
| 1717 | 1 1/2" (38 mm) | 7 1/4" (175 mm) | 2 1/4 (1 kg) | 30-60-95-125 | 115-230-360-475 |
| 1718 | 1 1/2" (38 mm) | 12" (295 mm) | 4 1/8 (1.9 kg) | 30-60-95-125 | 115-230-360-475 |
| 1720 | 1 1/2" (38 mm) | 9 1/2" (232 mm) | 4 (1.8 kg) | 30-60-95-125 | 115-230-360-475 |



1 1/2" Electrical Turbojet Nozzles

- Designed to be used on class "C" hazards
- No straight stream capabilities (min. 30° fog)

- 1715E** 1 1/2" Electrical Turbojet Nozzle
- 1720E** 1 1/2" Electrical Turbojet Nozzle with Pistol Grip



Style 1720E

| Style | Swivel Inlet | Length | Weight lbs. (kg) | Flow Settings | |
|-------|----------------|-----------------|------------------|---------------|-----------------|
| | | | | GPM | LPM |
| 1715E | 1 1/2" (38 mm) | 9 1/2" (232 mm) | 3 1/2 (1.6 kg) | 30-60-95-125 | 115-230-360-475 |
| 1720E | 1 1/2" (38 mm) | 9 1/2" (232 mm) | 4 (1.8 kg) | 30-60-95-125 | 115-230-360-475 |

