

**Unit Information**

Model #: 2206 / Item #07050  
UPC-IC (12 Digit): 01673070502

**Master Pack Dimensions**

Weight: 5.8 lbs. (2.6 kg)  
Cube: 0.93 ft<sup>3</sup> (0.02 m<sup>3</sup>)  
Quantity: 6

**Specifications**

Power Source: Alkaline or Carbon Zinc 6V  
Lantern Battery  
Bulb/Lamp: KPR 113  
Bulb/Lamp Life: 15 Hours  
Light Output: 50,000 Beam Candlepower  
Weight (Without batteries): 14.0 oz

**Components**

Lens Ring: Polypropylene (Black)  
Lens: Unbreakable Tuflexx®  
Reflector: Polycarbonate  
Lantern Box: Polypropylene (Safety Orange)  
Battery Connector: ABS, Spring brass & tin  
coated steel  
Switch: Rubber & co-polymer

**Product Features**

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Waterproof & floating
- Krypton Bulb
- Alkaline Battery
- Switch guard protects switch on impacts
- Optional stand
- Spare bulb compartments
- Oversized reflector for more light output
- Glove size handle
- Circuit Breaking Mechanism

**Unit Dimensions**

Length: 8.2 in. (20.9 cm)  
Width: 4.9 in. (12.4 cm)  
Height: 5.6 in. (14.2 cm)

**Safety Approvals**

UL/CUL: Class I, Div 1, Group C & D  
Class II, Div 1, Group G  
Operating Temp T3B  
CSA: Class I, Group C & D  
Class II, Group G  
Operating Temp T3A  
ASTM & MSHA Approved

