

BRIGHT STAR

The first name in flashlights.sm



Engineering Data Sheet: 2224

Unit Information

Model #: 2224 / Item # 14720

UPC-IC (12 Digit): 01673147204-

Master Pack Dimensions

Weight: 5.8 lbs. (2.6 kg)

Cube: 0.48 ft³ (0.014 m³)

Quantity: 12

Specifications

Power Source : Carbon Zinc Only: 3xD-cell

Bulb/Lamp: PR-3

Bulb/Lamp Life: 15 Hours

Light Output: 15,000 Beam Candlepower

Weight (Without batteries): 6.0 oz (.17 kg)

Components

Lens Ring: Polypropylene (Black)

Lens: Unbreakable Tuflexx®

Reflector: ABS

Tube: Polypropylene (Safety Orange)

Contact Strip: Spring brass & tin steel

Switch: Polypropylene

Bottom Cap: Polypropylene (Black)

Ring Hanger: ABS (Safety Orange)

Product Features

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Waterproof
- Spare bulb compartment
- Ring Hanger
- Three-way switch : On-Off-Flash
- Anti-roll tube
- Oversized, faceted reflector for more light
- Circuit breaking mechanism

Accessories

23853 6 1/2" Red Snap In Wand

23860 6 1/2" Yellow Snap In Wand

Unit Dimensions

Length: 10.2 in. (25.1 cm)

Width: 2.3 in. (5.8 cm) at head

Height: N/A

Safety Approvals

UL/CUL: Class I, Div 1, Group C & D

Div 2, Group A, B, C, & D

Class II, Div 1, Group G

Operating Temp T3C

CSA: Class I, Div 1, Group C & D

Class II, Div 1, Group G

Operating Temp T3C

ASTM & MSHA: Approved



**WorkSafe™ I Model
#2224**