



3%-6% AR-AFFF Foam Concentrate C361

Chemguard 3%-6% AR-AFFF is a specially formulated, aqueous film forming free flowing viscous foam concentrate. It forms a vapor suppressing aqueous film on hydrocarbon type fuels or a polymeric membrane on polar solvent/water miscible type fuels. It is intended for use at a proportioning rate of 3% (3 parts AR-AFFF concentrate to 97 parts water) on hydrocarbon fuels such as gasoline, kerosene, diesel etc. Chemguard 3%-6% AR-AFFF is intended for use at a 6% proportioning rate (6 parts AR-AFFF concentrate to 94 parts water) on polar solvent/ water miscible fuels such as alcohols, ketones, esters, etc.

FEATURES

- U.L. Listed, Foam Liquid Concentrates
- U.L. Canada Listed
- U.L. Listed for sub-surface injection
- Suitable for use with either fresh or salt water
- Excellent wetting characteristics when used in combating Class "A" fuel fires
- Suitable for use with carbon steel, fiberglass, polyethylene or stainless steel. Chemguard 3%-6% AR-AFFF is not compatible with galvanized pipe or fittings in an undiluted form.
- Suitable with dry chemical extinguishing agents
- Suitable for use on hydrocarbon or polar solvent type fuels
- Suitable for use with both air-aspirating foam and standard water fog nozzles

PROPORTIONING

- Fixed or portable in-line eductors
- In-line balanced pressure and pump pressure proportioning skid
- Bladder tank balanced pressure proportioning systems
- Around the pump proportioners
- Handline, air-aspirating nozzles with fixed eductor pickup tube

DISCHARGE DEVICES

- Foam Chambers
- Air-aspirating and non air-aspirating sprinkler heads or spray nozzles
- Standard water fog nozzles for handlines and monitors
- Air-aspirating foam nozzles
- Foam makers for use with either Floating Roof storage tanks or Dike/Bund protection systems.
- High back pressure foam makers for subsurface base injection system (hydrocarbon type fuels only)

FOAMING PROPERTIES

Aspirating type discharge devices typically generate expansion ratios between 6-10 to 1 when 3%-6% AR-AFFF is mixed with water at the correct ratio. Non-aspirating type devices will typically generate expansion ratios of between 2-4 to 1. Expansion ratios are dictated by the type of discharge device, flow rate and discharge pressure.

CHEMGUARD
204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606
www.chemguard.com

DESIGN INFORMATION

Cannot be used in sub-surface applications with polar solvent type fuels.

TYPICAL PROPERTIES AT 77°F (25°C)

Appearance.....Off White Gel-Like Liquid
Specific gravity.....1.016 g/ml
Ph.....7.0
Viscosity.....2500 cps*
*Brookfield[#]4 Spindle at 30 rpm

APPLICATION RATES

Recommend application rate on hydrocarbon type fuels is .10 gpm/ft.² and on polar solvent type fuels is .15 gpm/ft.². The recommended minimum application rates for the following specific polar solvent type fuels are:

IPA	0.15 gpm/ft ²
Methanol	0.12 gpm/ft ²
Ethanol	0.13 gpm/ft ²
Acetone	0.14 gpm/ft ²
Methyl Ethyl Keytone	0.13 gpm/ft ²
Ethyl Acetate	0.13 gpm/ft ²
MTBE	0.15 gpm/ft ²
Ethers	0.15 gpm/ft ²

ENVIRONMENTAL IMPACT

Chemguard 3%-6% AR-AFFF is biodegradable, low in toxicity and can be treated in sewage treatment plants. Please refer to Chemguard Technical Bulletin regarding foam products and the environment.

STORAGE

If kept in the original unopened and airtight Chemguard supplied container and stored within the temperature range of 35°F to 120°F(2°C-49°C), a shelf life of between 20-25 years can be expected. If the AR-AFFF is to be stored in an atmospheric type foam concentrate storage tank, whether on mobile apparatus or stationary, limit the air space above the surface of the concentrate when possible and place a layer of quality mineral oil on the surface of the foam concentrate to minimize any effect from evaporation.

ORDERING INFORMATION & WEIGHTS

Part No:	Container	Weight
C361P	5-Gallon Pail / 19 Liters	45 lbs.
C361D	55-Gallon Drum / 208 Liters	490 lbs.
C361BD	330-Gallon Tote / 1249 Liters	3000 lbs.

CHEMGUARD
204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • FAX (817) 473-0606
www.chemguard.com