

HIGH PERFORMANCE FIRE FIGHTING NOZZLE WITH FLOW RATE SELECTION

- Constant flow rate with all effects and at all flow rates.
- Ring for manual selection between 4 flow rates, without changing the effect.
- Manufactured in light and strong E-LITE material.
- Designed for working with foam injectors. The complementary CEP foam expander may be fitted.
- Cleaning system without changing the effect or needing to cut the water flow.
- Valve with anti-shock polymeric lever, available in 6 colours.

VIPER SG-1560. 50-125-200-230 lpm

NOZZLE:
1" BSP Swivel
Weight: 1,560 g
Length: 20 cm.

TIP:
1-1/2" BSP Swivel
Weight: 880 g.
Length: 15 cm.



VIPER SG-3012 115-230-360-475 lpm

NOZZLE:
1-1/2" BSP Swivel
Weight: 1,940 g.
Length: 22,5 cm

TIP:
1-1/2" BSP Swivel
Weight: 1,255 g.
Length: 15,5 cm.



NOTE:
The weights and dimensions of the nozzle include the necessary accessories for the fitting of "break away" nozzle

VIPER SG-7515 265 - 380 - 500 - 600 lpm

NOZZLE:
1-1/2" BSP Swivel
Weight: 1,940 g.
Length: 22,5 cm.

TIP:
1-1/2" BSP Swivel
Weight: 1,255 g.
Length: 15,5 cm.

VIPER SG-9520/1-1/2" 350 - 500 - 600 - 800 lpm

NOZZLE:
1-1/2" BSP Swivel
Weight: 2,980 g.
Length: 28,5 cm

TIP:
1-1/2" BSP Swivel
Weight: 1,720 g.
Length: 22 cm.

