

PORTABLE FIRE EXTINGUISHERS

15 LB CARBON DIOXIDE STORED PRESSURE FIRE EXTINGUISHERS

DESCRIPTION

Buckeye's 15 LB Carbon Dioxide fire extinguisher is used in "B" and "C" type fires.

It is ideal for chemical and manufacturing plants, oil rigs, rail yards, warehouses, construction sites, parking garages, airport ramps, boat docks and large laboratories.

FEATURES

- Manufactured to ANSI/UL 154 and ANSI/UL 711 standards.
- Marine / Vehicle Bracket Available
- US Coast Guard Approved for Type B:C Size II Valid Only with Bracket No. 810 P/N 700228.

SPECIFICATIONS

Buckeye's 15 LB Carbon Dioxide Fire Extinguisher meets the following specifications:

Capacity: 15 lbs / 6.80 kg

• **U.L. Rating:** 10 B:C

Chrome Plated Brass Valve

Ship Weight: 37 ¾ lbs 17.1 kg

• Height: 26 % in. / 67.0 cm

Width: 12 in. / 30.5 cm

• **Diameter:** 6 1/8 in. / 17.5 cm

Range: 4-8 feet / 1.2-2.4 meters

• Discharge Time: 15 seconds

• Cylinder: Aluminum

ORDERING INFORMATION

15 LB Carbon Dioxide wall Hook:

P/N 46100

(Refer to the Buckeye spare parts list for replacement parts)

